

Product Specification *

100% TCF (Totally Chlorine Free)

Grammage (g/m ²) ISO 536	54	57	60	65	70	80
Brightness % ISO 2470 D65	76	78	78	78	78	78
Opacity % ISO 2471	91	91.5	92.5	93.5	94.5	96
Gloss, % T480 Hunter 75°	49	50	53	53	54	54
Bulk, cm³/g	1.0	1.0	1.0	1.0	1.0	1.0
L*, % ISO 5631 D65 C/2	89	90	90	91	91	91
a*, % ISO 5631 D65 C/2	-0.4	-0.3	-0.3	-0.3	-0.3	-0.3
b*, % ISO 5631 D65 C/2	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0

*The values given are target values and variations occur.

Producer

SCA Ortviken, Sweden.

Areas of applications

Magazines, supplements and inserts printed in heatset web offset.

Reel diameters

Standard diameters are 100, 120 and 125 cm.
(Machine width max 7.74 m.)

Reel width

The minimum reel width which can be produced is 400 mm.

Web length

Approximately:

g/m ²	54	57	60	65	70	80
Ø 100 cm	15 500	15 000	14 000	13 000	12 200	11 000
Ø 120 cm	22 500	21 500	20 500	18 000	17 700	16 000
Ø 125 cm	24 500	23 500	22 000	19 000	19 100	18 000

Environment

TCF (totally chlorine-free) and certified in accordance with ISO 9001 and 14001. Chain of Custody in accordance with FSC and PEFC.

Wrapping

Reels are wrapped in polyethene laminated liner inner endshields of corrugated board and polyethene coated outer endshields.

Packing

Reels less than 600 mm in width are always co-packed.

Surface pH value

The surface pH value of the paper is >6.

Rev. 2012-02-16

For further information and samples, please contact

SCA ORTVIKEN

SCA Graphic Sundsvall AB
Box 846
SE-851 23 SUNDSVALL
www.publicationpapers.sca.com

