

## Product Specification \*

100% TCF (Totally Chlorine Free)

Grammage (g/m <sup>2</sup> ) ISO 536	57	60	65	70
<b>Brightness, %</b> ISO 2470 D65	80	80	80	80
<b>Opacity, %</b> ISO 2471	93	94	95	96
<b>Gloss, %</b> T480 Hunter 75°	30	30	30	30
<b>Bulk, cm<sup>3</sup>/g</b>	1.1	1.1	1.1	1.1
<b>L*, %</b> ISO 5631 D65 C/2	90	91	91	92
<b>a*, %</b> ISO 5631 D65 C/2	-0.2	-0.2	-0.2	-0.2
<b>b*, %</b> ISO 5631 D65 C/2	-1.0	-1.0	-1.0	-1.0

\*The values given are target values and variations occur.

### Producer

SCA Ortviken, Sweden.

### Areas of applications

Magazines, supplements and inserts printed in heatset web offset.

### Reel diameters

Standard diameters are 100, 120 and 125 cm.  
(Machine width max 7.74 m.)

### Reel width

The minimum reel width which can be produced is 400 mm.

### Web length

Approximately:

g/m <sup>2</sup>	57	60	65	70
Ø 100 cm	13 500	13 000	11 500	11 000
Ø 120 cm	19 500	18 500	16 500	15 500
Ø 125 cm	21 000	20 000	18 000	17 500

### Environment

TCF (totally chlorine-free) and certified in accordance with ISO 9001 and 14001. Chain of Custody in accordance with FSC and PEFC.

### Wrapping

Reels are wrapped in polyethene laminated liner with inner endshields of corrugated board and polyethene coated outer endshields.

### Packing

Reels less than 600 mm in width are always co-packed.

### Surface pH value

The surface pH value of the paper is >6.

Rev. 2012-02-16

For further information and samples, please contact

### SCA ORTVIKEN

SCA Graphic Sundsvall AB  
Box 846  
SE-851 23 SUNDSVALL  
[www.publicationpapers.sca.com](http://www.publicationpapers.sca.com)

