

Technical target values

Grammage (g/m ²) ISO 536	49	52
Brightness, % ISO 2470 D65	72	72
Opacity, % ISO 2471	91	92
Bulk, cm ³ /g ISO 534	1.6	1.6
L* ISO 5631 D65	88.4	88.4
a* ISO 5631 D65	-1.2	-1.2
b* ISO 5631 D65	2.6	2.6

The values given are target values and variations occur.

Producer

SCA Ortviken, Sweden.

Areas of applications

High-bright uncoated offset paper with high bulk, which give stability even with few pages. For supplements advertising matter and periodicals in coldset and heatset web offset.

Reel diameters

Standard diameters are 100, 115 and 125 cm.

Reel width

Available range is 370 - 2860 mm.

Core

76 and 152 mm

Approx. web length

g/m ²	49	52
Ø 100 cm	11 200	10 700
Ø 115 cm	11 200	14 100
Ø 125 cm	17 600	16 800

Environment

The mill is certified in accordance with ISO 9001 and 14001. Chain of Custody in accordance with FSC and PEFC.

Wrapping

Reels are wrapped in polyethene laminated liner with inner end shields of corrugated board and polyethene coated outer end shields.

Packing

Reels less than 600 mm in width are always co-packed and marked with a red stripe.

Surface pH value

The pH value of the paper is >6.

For colour profile information, please contact the technical service representative at your local sales office.

Rev. 2018-09-06

For further information and samples, please contact:

SCA ORTVIKEN

SCA Graphic Sundsvall AB

Box 846

SE-851 23 SUNDSVALL

www.sca.com/publicationpapers