



Selected heartwood

WINDOW INDUSTRY

Heartwood graded pine is particularly suited for the outside of the window, which is affected more by weather conditions. Fulfils DVC (Dansk Vindues Certificering).

- Guaranteed heartwood percentage
- Tight growth rings, higher durability
- Lower impregnation requirement
- Relax drying technology

WINDOW INDUSTRY

Dimensions

Thickness: Customer-selectable.
Width: Customer-selectable.
Length: Packaged to length. Exact cut.

Wood type

Pine.

Moisture content

Customer-selectable (12, 16 %). Relax drying technology.

Raw material

Butt log. The base of raw materials to SCA Wood's product programme is supplied from SCA's own forest holdings in northern Sweden. SCA's forestry operations are certified in accordance with the standards of the FSC® (Forest Stewardship Council) and PEFC™ (Programme for the Endorsement of Forest Certification).

Other

Please contact us if you need products outside the standard selection.
Welcome to visit us at sca.com.



Laminated blanks

Laminated blanks are sawn and planed pine components glued in two or more layers.

- Customer-selectable
- Finger-jointed
- High shape stability
- Defect-free
- Relax drying technology

Dimensions	Thickness: Customer-selectable. Width: Customer-selectable. Length: 5,4-6,0 meter. Exact cut up to GMT.
Wood type	Pine.
Moisture content	Customer-selectable (9, 12 %). Relax drying technology.
Raw material	Butt log. The base of raw materials to SCA Wood's product programme is supplied from SCA's own forest holdings in northern Sweden. SCA's forestry operations are certified in accordance with the standards of the FSC® (Forest Stewardship Council) and PEFC™ (Programme for the Endorsement of Forest Certification).
Other	Please contact us if you need products outside the standard selection. Welcome to visit us at sca.com .



Solid finger-jointed blanks

Solid finger-jointed blanks are produced from original-sawn, green or dry split raw materials that are planed, cut to grade and finally finger-jointed to longer lengths. Can also be special cut.

- High level of customization
- Exact cut
- Green split and pith-free

Dimensions

Thickness: Customer-selectable (50/63/75 mm).
Width: Customer-selectable (63/75/87/90/100 mm).
Length: 5,4-6,0 meter. Exact cut.

Wood type

Pine.

Moisture content

Customer-selectable (12, 16%). Relax drying technology.

Raw material

Butt log, A-class. The base of raw materials to SCA Wood's product programme is supplied from SCA's own forest holdings in northern Sweden. SCA's forestry operations are certified in accordance with the standards of the FSC® (Forest Stewardship Council) and PEFC™ (Programme for the Endorsement of Forest Certification).

Other

Please contact us if you need products outside the standard selection.
Welcome to visit us at sca.com.